

**STARBORN®**

**CAP-TOR® xd**

**Color Matched Screws for Composite and PVC Decking**



CAP-TOR xd COLOR		DECKING BRAND COLOR		
		AZEK	DECKORATORS	TIMBERTECH
	<b>#31 TAN-GRAY</b>	WEATHERED TEAK	COSTA	
	<b>#34 BROWN</b>	ENGLISH WALNUT MAHOGANY	MESA	BROWN OAK DARK ROAST DARK TEAK
	<b>#37 GRAY</b>	CASTLE GATE COASTLINE		ASHWOOD DRIFTWOOD MARITIME GRAY SILVER MAPLE STONE ASH
	<b>#43 ASHWOOD</b>			WHITEWASH CEDAR
	<b>#53 DARK GRAY</b>		DUSK RIDGELINE SIERRA	
	<b>#54 WARM GRAY</b>	SLATE GRAY	TUNDRA	
	<b>#55 DARK SLATE</b>		SLATE	
	<b>#63 BUCKSKIN</b>			ANTIQUE LEATHER TIGERWOOD
	<b>#64 SAND</b>	BROWNSTONE FRENCH WHITE OAK		
	<b>#65 ROSY BROWN</b>			PECAN
	<b>#71 CHOCOLATE</b>	AMERICAN WALNUT DARK HICKORY KONA	KYAYA PATHWAY	ESPRESSO
	<b>#73 JAVA</b>			MOCHA RUSTIC ELM
	<b>#81 CEDAR</b>		SEDONA	



**CAP-TOR<sup>®</sup> xd**

**Color Matched Screws for Composite and PVC Decking**

<p><b>1. Star Drive</b> Favored by professionals; extra deep recess reduces cam-out.</p>		<p><b>1. Star Drive</b> Favorecido por los profesionales; El rebaje extra profundo reduce la salida de la leva.</p>
<p><b>2. Undercut Head</b> Cleanly penetrates the hard outer layer of capstock decking.</p>		<p><b>2. Undercut Head</b> Penetra limpiamente la capa exterior dura de la plataforma de capstock.</p>
<p><b>3. Reverse Thread</b> Prevents mushrooming and other surface defects.</p>		<p><b>3. Reverse Thread</b> Previene la formación de hongos y otros defectos superficiales.</p>
<p><b>4. Tri-Lobe Shank and Acute Thread Angle</b> For increased driving power and cleaner penetration through harder decking materials.</p>		<p><b>4. Tri-Lobe Shank and Acute Thread Angle</b> Para una mayor potencia de conducción y una penetración más limpia a través de materiales de cubierta más duros.</p>
<p><b>5. Type 17 Auger Tip</b> For faster, easier entry; helps prevent splitting.</p>		<p><b>5. Type 17 Auger Tip</b> Para una entrada más rápida y fácil; ayuda a prevenir la división.</p>
<p>Depth Setter Compatible Collated available</p>	<p>Compatible con medidor de profundidad Compaginado disponible</p>	

Installation	Instalación
<p>Install flush with decking surface. Do not overdrive.</p>	<p>Instale al ras con la superficie de la terraza. No conduzca en exceso.</p>
<p>Install two screws per joist.</p>	<p>Instale dos tornillos por viga.</p>
<p>Predrilling is recommended when fastening within 1" from the end of a deck board.</p>	<p>Se recomienda perforar previamente cuando se fija dentro de 1" desde el extremo de una tabla de plataforma.</p>
<p>Recommended: For a clean and professional finish use the SMART-BIT<sup>®</sup> Depth Setter Tool in combination with screws.</p>	<p>Recomendado: Para un acabado limpio y profesional, use la herramienta de ajuste de profundidad SMART-BIT<sup>®</sup> en combinación con tornillos</p>

